

# 5 YEAR MIIG-WARRANTY

## FIND OUT HOW WE ARE DIFFERENT

### DYNAMIC DFU

Repair - upgrade online  
saves downtime & cost

### UP TO 90 DAYS

Calibration due date reminder  
option

### HIGH BIT 0.01 RESOLUTION

Measures & represents smallest  
process changes

### EACH CHANNEL 4 ALARMS

All channel having 4 nos audible &  
visual alarms

### PROGRAMMABLE DISPLAY

Display is programmable as per  
process requirement

### NO ONE BY ONE - 50 AT A TIME

Programming, online view & report  
for 50 units in 1 go

### LARGE MEMORY

High-Speed Logging Up to 78k data  
memory with 1 sec - 24 hrs logging  
interval

### 3 - 5 - 10 POINTS

Drift adjustment & calibration option  
complete graph correction

### PREMIUM ACCURACY

%RH :  $\pm 0.5\%$  RH, Temp :  $\pm 0.1$  °C.  
other parameters (Refer catalogue)

### ONLINE MONITORING

Bluetooth ~ wi-fi ~ rs485  
gsm-gprs ~ ethernet

### JUDGEMENT TIME ALARM

Intelligent logic alarm function for  
each channel

### SENSOR REPLACEMENT

Don't discard the complete unit, if  
sensor is damaged

### MKT REPORT

Get MKT report for total period or  
selected period

### APPLICATIONS & SOFTWARES

Mobile - PC- Cloud Application &  
Software in Professional + 21 CFR  
version



## BLE ENABLED DIGITAL THERMO HYGROMETER & DATA LOGGERS

online - offline monitoring via mobile app or pc software



**BLUE-H-B SERIES** Digital Thermo Hygrometer & **BLUE-H-A SERIES** DATA LOGGERS are Bluetooth-enabled Online + Offline portable, battery-operated programmable devices that can go up to 4 channels to address various applications

**PARAMETER :** %RH-Temp (Internal + External), External Temperature Sensor

**ACCURACY:**  $\pm 1\%$  RH &  $\pm 0.2\text{ }^{\circ}\text{C}$

**RESOLUTION:** 0.01% RH & 0.01 $^{\circ}\text{C}$

5 YEARS WARRANTY  
& ONLINE REPAIR FEATURE

3 - 5 - 10 POINT DRIFT  
ADJUSTMENT & CALIBRATION

BULK OPERATION OF UP TO  
50 DEVICES VIA BLUE DOCK

### FEATURES:

- Sensor element replacement possible (if damaged)
- Thermo Hygrometers - with up to 60 days of statistical recording (MAX-MIN-AVG) on automatic mode on a FIFO basis
- Data Loggers - with 1 ch (40k), 2 ch (60k), 3 ch (72k), 4 ch (78k) memory
- Up to 15 alarm logs (FIFO) On The Device Display and report. It helps the user to tune HVAC for optimum performance
- Programmable Display features allow users to keep the desired parameters as per SOP and that helps them during AUDIT
- An automatic report processing in PDF (optional CSV) eliminates the possibility of manipulations
- Online real-time monitoring, group programming / downloading up to 50 devices in clicks with BLUE-DOCK device.
- Contact us to learn all 30+ features

21 CFR COMPLIANT HYGROMETER & DATA LOGGER

## DIFFERENT APPLICATIONS

### SINGLE SOURCE SOLUTION

#### **BLUE-H-B/A-THIE + MO-RHE Sensor**

DESCRIPTION: With internal + External %RH-Temp sensor. Useful for room and outside room monitoring purposes with 30+ features. External sensor with up to 3 meters cable.



#### **BLUE-H-B/A-THE + MO-RHX Sensor**

DESCRIPTION: With External %RH-Temp sensor. Useful, where the display stays outside and the sensor goes to the application environment. External sensor with up to 3 meters cable.



#### **BLUE-H-B/A-T2 + MI-DTC Sensor**

DESCRIPTION: With 2 nos. External Temp sensor. Useful for freezer / deep freezer or similar types of monitoring purposes with 30+ features. External sensor with up to 5 meters cable.



#### **BLUE-H-B/A-T1 + MI-DTC Sensor**

DESCRIPTION: With External Temp sensor. Useful for freezer / deep freezer or similar types of monitoring purposes with 30+ features. External sensor with up to 5 meters cable.



#### **BLUE-H-B/A-THIT2 + MI-DTC Sensor**

DESCRIPTION: With internal %RH-Temp sensor & 2 nos external Temp. sensor for room and 2-point temp. monitoring purpose with 30+ features. External sensor with up to 5 meters cable.



#### **BLUE-H-B/A-THIT1 + MI-DTC Sensor**

DESCRIPTION: With internal %RH-Temp sensor & 1 no. external Temp. sensor for room and 1 point temp. monitoring purpose with 30+ features. External sensor with up to 5 meters cable.



## ARE YOU WORRIED ABOUT HARSH ENVIRONMENT?



If your monitoring location is not inside a cleanroom - RATHER IT IS IN OPEN ATMOSPHERE - Don't worry, we have the solution for outdoor applications too.

**We can also provide a relay to activate HOOTER.**



## BLE ENABLED ONLINE REAL-TIME INDICATOR CUM DATA LOGGERS

**BLUE-S-B SERIES**  
**1-2 channel** Bluetooth-enabled Online + Offline portable, battery-operated Thermal Mapping/ Validation Datalogger.



**BLUE-W-B SERIES**  
**1-4 channel** Bluetooth-enabled Online + Offline STANDALONE data logger.

**ACCURACY:**  $\pm 1\%$  RH &  $\pm 0.2^\circ\text{C}$

**RESOLUTION:** 0.01% RH & 0.01 $^\circ\text{C}$

### How are we unique



PC SOFTWARE



MOBILE SOFTWARE

- 5 YEARS MIIG-WARRANTY
- Ultra high-speed data logging from 1 sec to 24 hours with 40k (1 ch), 60k (2 ch), 72k (3 ch) and 78k (4 ch) memory
- 3-5-10 Point drift adjustment feature helps the user to regain premium accuracy every time they go for re-calibration until the sensor is alive. Miigo provides a Standard salt solution with NIST traceability
- ONLINE REAL-TIME ACCESS: View live data, and alarms over MIIG-BLUE mobile applications or BLUE-DESK PC software.
- AUDIBLE ALARM + VISUAL LED ALARM WITH JUDGEMENT TIME FUNCTION: For each parameter with 2 nos real alarm and 2 nos pre-alarm points (HH-H-L-LL).
- For all 30 features, refer the catalogue

INTERNAL OR EXTERNAL %RH-TEMP

INTERNAL OR EXTERNAL TEMP SENSOR (RTD/TC)

**PORTABLE DATA LOGGER FOR VARIOUS APPLICATIONS WITH REAL  
-TIME DATA TRANSFER VIA BLUETOOTH IN MOBILE APPLICATION / PC SOFTWARE**



**BLUE-S-B-LUXE** series  
Bluetooth-enabled online battery-operated lux meter with  $\pm 2\%$  accuracy and 0.1/1 lux resolution.

**BLUE-S-B-CO2E** series  
Bluetooth-enabled online Power-operated CO2 & Temperature data logger.  
KNOW MORE....

**BLUE-S-B-DPI/E** series  
Bluetooth-enabled online battery-operated DIFFERENTIAL PRESSURE data logger. KNOW MORE....

**BLUE-S-B-CX/VX** series  
Bluetooth-enabled online battery-operated Current and voltage data logger, KNOW MORE....

DIFFERENTIAL PRESSURE

CURRENT & VOLTAGE

LUX

ABSOLUTE PRESSURE


CO2

OTHER PARAMETERS  
ON REQUEST

**A PORTABLE DEWPOINT MONITORING DEVICE  
WITH DATA LOGGING AND ALARMS**

**BLUE-P-DEW (PORTABLE DEW POINT METER):** Bluetooth enabled Online + Offline battery-operated Portable Dewpoint indicator cum datalogger with a dewpoint range of  $-70...85$  °C Td. It comes with an accuracy of  $\pm 2$  °C Td ( $-50...20$  °C Td)  $\pm 3.5$  °C Td ( $-60...-50$  °C Td). and 0.01 resolution.

**PARAMETER-** Temperature and Pressurized Dew point up to 16 / 100 Bar



5 YEARS WARRANTY  
& ONLINE REPAIR FEATURE

3 - 5 - 10 POINT DRIFT  
ADJUSTMENT & CALIBRATION

MOBILE & PC SOFTWARE FOR  
DOCUMENTATION

**FEATURES: 30+ Features with PC Software & Mobile Application**

## LAB MASTER: BLE-ENABLED ONLINE REAL-TIME REFERENCE CLASS MASTER %RH-TEMP INDICATOR CUM DATA LOGGERS

**BLUE - P - THER** is a portable battery-operated Reference Class %RH-Temperature Master instrument. Mainly used for Calibration and spot-checking purposes with range Humidity: 0 to 100% RH, Temperature: -50.00 to 100.00 °C, Dew Point (Calculated): -40 to 70 °C

PREMIUM MASTER ACCURACY: 0.8% RH &  $\pm 0.1$  °C  
**(CAN BE UPGRADABLE TO  $\pm 0.5$  % RH)**  
RESOLUTION OF 0.01 %RH / 0.01 °C



### HOW ARE WE UNIQUE

- 5 YEARS MIIG-WARRANTY
- optional High-Temperature sensor comes with -100 to 200 °C range.
- Ultra high-speed data logging from 1 sec to 24 hours with 60,000 memory
- 3-5-10 Point drift adjustment feature helps the user to regain premium accuracy every time they go for re-calibration until the sensor is alive.
- ONLINE REAL-TIME ACCESS: View live data, and alarms over MIIG-BLUE mobile applications or BLUE-DESK PC software.
- AUDIBLE ALARM + VISUAL LED ALARM WITH JUDGEMENT TIME FUNCTION: For each parameter with 2 nos real alarm and 2 nos pre-alarm points (HH-H-L-LL).
- About 30 days+ battery back-up for long site activities.
- For all 30 features, refer the catalogue

a perfect tool for  
**HUMIDITY AND TEMPERATURE CALIBRATION**



**IF ARE YOU WORRIED ABOUT THE ACCURACY OF THE BLUE-P-THER,  
OPT FOR A CALIBRATION-SALT SOLUTION AND CALIBRATION CHAMBER**

Whenever there is a critical calibration initiation, the user can use NIST certified salt solution to ensure the accuracy of the master instrument, whether deviated or not.

Using the 3 - 5 - 10 points drift adjustment method, the user can perform correction of the master at the site itself.



**MEASURING %RH-TEMP IN H2O2 ENVIRONMENT  
IS NO MORE A CHALLENGE WITH MIIGO ONLINE LLP**

**BLUE-P-H2O2:** Bluetooth enabled Online + Offline battery-operated Portable humidity & temperature indicator cum datalogger for measurement in H2O2 environment with an Accuracy of  $\pm 0.8\% RH$  and  $\pm 0.1\text{ }^\circ C$  with 0.01 resolution.

**FEATURES:** 30+ Features with online real-time monitoring via PC Software & Mobile Application

**PARAMETER** - Humidity, Temperature and calculated dewpoint in **H2O2 ENVIRONMENT.**



**5 YEARS WARRANTY & ONLINE REPAIR FEATURE**

**3 - 5 - 10 POINT DRIFT ADJUSTMENT & CALIBRATION**

**ONLINE REAL-TIME MONITORING**

**APPLICATIONS**  
Bio-decontamination in Isolators, cRABS, Transfer Hatches, Hospitals (Critical Care Areas), Aircraft, Critical Cleanrooms and all other applications having the requirement of decontamination.

**LAB MONITOR: BLE ENABLED ONLINE INDICATOR CUM DATA LOGGERS WITH ONLINE REAL-TIME MONITORING**



**MODEL BLUE-P-THITAP** comes with Absolute Pressure, Humidity, internal and external temperature and calculated dewpoint measurement.



**MODEL BLUE-S-B-ABSI** comes with Absolute Pressure and Temperature.



**MODEL BLUE-P-THIAP** comes with Absolute Pressure, Humidity, internal temperature and calculated dewpoint measurement.

**ACCURACY:**  $\pm 1\%$  RH &  $\pm 0.2^\circ\text{C}$  ABSOLUTE PRESSURE  $\pm 2.5$  HPA, TEMP (EXT)  $\pm 0.3^\circ\text{C}$   
**RESOLUTION:** 0.01% RH & 0.01 $^\circ\text{C}$  (INT), 0.1/1 HPA, 0.01/0.1  $^\circ\text{C}$  (EXT)

Model / Parameter	Humidity	Temperature (Internal)	Dew Point	Absolute Pressure	Temperature (External)
BLUE-S-B-ABSI	NO	YES	NO	YES	NO
BLUE-P-THIAP	YES	YES	YES	YES	NO
BLUE-P-THITAP	YES	YES	YES	YES	YES

**APPLICATIONS**

Ideal Device For Monitoring Of Calibration Lab / Production Area / Process Area / R&D Lab And Various Other Applications.



**5 YEARS WARRANTY & ONLINE REPAIR FEATURE**

**3 - 5 - 10 POINT DRIFT ADJUSTMENT & CALIBRATION**

**ONLINE REAL-TIME MONITORING**

**For all 30 features, refer the catalogue**



**100% BATTERY-OPERATED WI-FI DATA LOGGER**  
IDEAL FOR THERMAL MAPPING / VALIDATION APPLICATION



**BLUE-S-WB SERIES BATTERY -OPERATED PORTABLE WI-FI DATA LOGGERS WITH**

- MEMORY : On device 40k (1 Ch) and 60K (2 Ch)
- Dynamic DFU chip : allow online repairing (without sending the unit to factory)
- ALARM : Audible + Visual Alarm + Judgement Time function
- PROGRAMMABLE DISPLAY : The user can programmable the display parameter based on requirements out of %RH-Temp- Dewpoint - Date - Time.
- LOGGING INTERVAL : 1 sec - 24 Hours, TRANSFER TIME : 5 min and above
- INSTANT ALARM : Immediate Alarm, irrespective of logging or transfer rate
- BATTERY LIFE : 6 months over primary cell / 2 months over rechargeable cell  
OPTION to connect PT 100 / PT100 / Thermocouple Sensors

**ACCURACY:**  $\pm 1\%$  RH &  $\pm 0.2^{\circ}\text{C}$

**RESOLUTION:** 0.01% RH & 0.01 $^{\circ}\text{C}$

5 YEARS WARRANTY  
& ONLINE REPAIR FEATURE

3 - 5 - 10 POINT DRIFT  
ADJUSTMENT & CALIBRATION

SENSOR ELEMENT  
REPLACEMENT OPTION

PC SOFTWARE (NO  
REQUIREMENT OF INTERNET)

CLOUD SOFTWARE ON MIIGO  
SERVER ( REQ. INTERNET)

MQTT PROTOCOL - ON  
CUSTOMER SERVER

**ONLINE REAL-TIME MONITORING, DOCUMENTATION  
AND LIVE ALARM VIA SMS / WHATSAPP / CALL / EMAIL + REMOTE HOOTER**

**BLUE-W-W** comes with 1-4 Channel universal input and **WI-FI OUTPUT**

**BLUE-W-R** comes with 1-4 Channel universal input and **RS485 OUTPUT**


**BLUE-W-G** comes with 1-4 Channel universal input and **GSM-GPRS OUTPUT**

**BLUE-W-E** comes with 1-4 Channel universal input and **ETHERNET OUTPUT**

- %RH-Temp (internal + external)
- Temperature (NTC/PT100/PT1000/ TC) -(internal + external)
- Lux Sensor (external)
- Differential Pressure (internal + external) sensor
- Absolute Pressure - temp internal sensor
- 4- 20 mA Current Input
- 0 - 1/3.6/5/10 VDC input
- Other Parameters on request



- **MEMORY** : On device 40k for 1 Ch and 60K for 2 Ch, 72K for 3 Ch and 78K for 4 Ch device.
- **ALARM** : Audible + Visual Alarm + Judgement Time function
- **PROGRAMMABLE DISPLAY** : The user can programmable the display parameter based on requirements out of %RH-Temp- Dewpoint - Date - Time.
- **LOGGING INTERVAL** : 1 sec - 24 Hours, **TRANSFER TIME** : 1 min and above,
- **INSTANT ALARM** : Immediate Alarm, irrespective of logging or transfer rate



**5 YEARS WARRANTY  
& ONLINE REPAIR FEATURE**

**3 - 5 - 10 POINT DRIFT  
ADJUSTMENT & CALIBRATION**

**SENSOR ELEMENT  
REPLACEMENT OPTION**

**PC SOFTWARE (NO  
REQUIREMENT OF INTERNET)**

**CLOUD SOFTWARE ON MIIGO  
SERVER ( REQ. INTERNET)**

**MQTT PROTOCOL - ON  
CUSTOMER SERVER**

# 10+

## REASONS TO GO FOR MIIGO



**SENSOR ELEMENT REPLACEMENT FEATURE :** In most cases, it is observed the sensor element gets damaged due to harsh application, We have an option for replacement of the sensor element and use the same unit over and again.

### BENEFITS BEFORE PURCHASE

**RUGGED CONSTRUCTION :** Each unit comes with rugged construction with an SS sintered filter to address the worst environment.

**ACCURACY :** HUMIDITY:  $\pm 1\%$  RH, TEMPERATURE:  $\pm 0.2$  °C (NTC sensor) or Class-A accuracy for PT-100 / PT-1000 element and ABSOLUTE PRESSURE:  $\pm 2.5$  HPA

**RANGE :** It comes with 0-100% RH, - 40 TO 70 °C, and 300 TO 1200 HPA (based on the model selected)

**OUTPUT :** RS485 | 4-20MA | 0-1/3.6/5/10 VDC

**POWER SUPPLY :** From 8 VDC to 60 VDC

**CONNECTION TYPE :** 2/3 wire (pre-ordered)

**MIIG-CONFIGURATOR :** A free tool to configure the Slave ID, and Boud Rate for the RS485 output version. The same tool can be used for Current (4-20mA) + Voltage Output version sensors to change the output range.


### POST-PURCHASE (ROI)

**5 -YEAR MIIG-WARRANTY :** Standard supply comes with 1 year of warranty. However, users can request an extension of up to 5 years

**OPEN CONNECTOR MODULE :** Helps user to extend/reduce cable at the site itself (up to 200 meters for RS485 Version / Up to 50 meters for 4-20mA Version / up to 10 meters for voltage Output Version)

**3- 5-10 POINTS DRIFT ADJUSTMENT + CALIBRATION :** This helps you to correct the sensors when drift occurs after continuous usage. Using this feature users can remove the drift and use the sensor as a nearly new one.

**CALIBRATION AUTHENTICITY :** Whenever the unit goes for calibration, the user can check if the calibration lab has practically done the calibration and adjustment or submitted a fake certificate.



**MI-WS SERIES :** weather shield or solar radiation shield used for weather monitoring applications

#### FEATURE :

- Diameter: 165mm
  - Length: 150mm
  - Material: Weather-proof Polystyrene + Acrylic
  - Plates: 8 Nos
  - Internal sensor insertion dia 29mm
- Supplied with mounting plate and holding bracket for 1.5"/2" pipe mounting.

## BLUE-X SERIES

## BLUE-XS SERIES

TRANSMITTER

CONTROLLER

DATA LOGGER

HYGROMETER



### 10+ REASONS TO GO FOR BLUE - X AND BLUE - XS SERIES

**ACCURACY:**  $\pm 0.8\%$  RH &  $\pm 0.1\text{ }^{\circ}\text{C}$

**RESOLUTION:** 0.01% RH & 0.01 $^{\circ}\text{C}$

5 YEARS WARRANTY  
& ONLINE REPAIR FEATURE

3 - 5 - 10 POINT DRIFT  
ADJUSTMENT & CALIBRATION

OPTION AVAILABLE FOR PC  
SOFTWARE/CLOUD SOFTWARE

USER CONFIGURABLE OUTPUT  
RANGE TO MATCH YOUR SETTING

WIDE RANGE OF TEMPERATURE  
TEMP FROM - 100 TO 200  $^{\circ}\text{C}$

LED LIGHT & AUDIBLE INBUILT  
BUZZER FOR LOCAL ALARM

O/P - CURRENT/VOLTAGE/WI-FI  
RS485/ETHERNET/GSM-GPRS

COMES IN WALL / DUCT /  
REMOTE MOUNT TYPES

OPTIONAL 5 AMPS - 230 VAC  
RELAY AS CONTROL / HOOTER

### SENSOR ELEMENT REPLACEMENT OPTION

In most cases, it is observed the sensor element gets damaged due to harsh application, We have an option for replacement of the sensor element and use the same unit over and again.

**BLUE-X SERIES** and **BLUE-XS series** can be integrated with different types of sensors based on the applications with blind type or with local display, data logging, Buzzer, Relay output and so on

- RH : 0 to 100% RH / Acc.  $\pm 0.8\%$  / Res. 0.01% RH
- Temp. : -100 to 200  $^{\circ}\text{C}$  / Acc.  $\pm 0.1\text{ }^{\circ}\text{C}$  / Res. 0.1/0.01 $^{\circ}\text{C}$
- Dew Point (Calculated): -40 to 70  $^{\circ}\text{C}$  / Res. 0.01 $^{\circ}\text{C}$

Stability Chamber, Clean Room, Cold Storages, Fluid Bed Drier (FBD) - all kinds of applications can be covered.



**BLUE-X SERIES** and **BLUE-XS series** multi-utility devices can be integrated with different types of dewpoint sensors with blind type or with Local display, data logging, Buzzer, Relay output and so on.

Dew Point (Calculated): -40 to 70  $^{\circ}\text{C}$  / Resolution 0.01 $^{\circ}\text{C}$   
pressure up to 400bar

Dewpoint measurement of Compressed air, Oxygen, SF6 and various types gas (of non-hazardous) applications can be covered.

**CAN BE INTEGRATED WITH ANY OTHER PARAMETERS**



**POWERFUL ACCESSORIES**

MAKE THIS UNIT MORE INTEGRATED TO PROCESS

**ACCESSORIES THAT SAVES TIME FOR TEAM**

**PART CODE: BLUE-DOCK-TFT-4.3-H**  
**MAKE: MIIGO ONLINE LLP**  
**HSN CODE: 90258090**



Hand-held battery-operated 4.3" TFT touchscreen display device.

- Programming of 50 devices in 5 groups
- View live data and alarm on screen for connected devices
- Direct PDF report of statistical values for up to 50 Hygrometers without any software
- Direct PDF report of data logging for up to 50 data loggers without any software
- Optional BLUE-DESK-PROF PC software to download data in PDF + Excel format
- Optional BLUE-DESK-CFR PC software to download data in Non-editable PDF format
- Buzzer for alarms

The power adapter MODEL: MI-ADOP-IND is to be purchased separately (compulsory)  
 Applicable for BLUE-H, BLUE-P, BLUE-S, BLUE-W SERIES ONLY  
 BLUETOOTH VERSIONS

**CONSOLIDATED VIEWING PLATFORM & HARD HOOTER / RELAY**

**PART CODE: BLUE-term-TFT-7-p**  
**MAKE: MIIGO ONLINE LLP**  
**HSN CODE: 90258090**




Panel-mounted 7" TFT touchscreen display device

- View live data and alarm on screen for connected devices
- LOUD internal buzzer
- Live data for 50 Bluetooth-enabled devices / 16 Wi-fi enabled devices
- Optional relay output - The user can connect Loud Hooter

The power adapter MODEL - MI-ADOP-IND is to be purchased separately (compulsory)  
 Applicable for BLUE-H, BLUE-P, BLUE-S, BLUE-W SERIES BLUETOOTH + WI-FI version

**MOBILE APP - PC SOFTWARE - CLOUD APP**  
 MAKE THIS UNIT MORE INTEGRATED TO PROCESS

**CLUB MULTIPLE ROOMS DATA DISPLAY IN SINGLE MONITOR WITH LOCAL BUZZER AND HOOTER (OPTIONAL)**





**WAREHOUSE**



**PHARMACEUTICAL**



**COLD STORAGE**



**CLEAN ROOMS**



**SUPER MARKET**



**FOOD MFG**

## **INDUSTRY WE ARE INTO**



**SERVER ROOM MONITORING**



**AUTOMOBILE**



**CRO AND R&D LABS**



**PHARMACY**



**HOSPITAL**



**BLOOD BANK**



**COTTON MILL**




**PAPER INDUSTRY**



**MUSEUM**



**GREEN HOUSE**



**ELECTRONIC MFG**



**TOBACCO MFG**

# **INDUSTRY WE ARE INTO**



**SPINNING MILL**



**CONTROL ROOM**




**PROJECT COMPANY**



**CHEMICAL MILL**



**CALIBRATION LAB**



**CALIBRATION  
& VALIDATION**

**SERVICE PROVIDER**

# ABOUT US



## WE STARTED

Our Journey Started In Sep 2020 With 6 Passionate Colleagues Who Dreamed Of Delivering A Premium Choice To Industry.



## OUR VISION

We Wish, We Could Deliver Solutions For Every Problem In The Process And If Not All, Then At The Max- Till Our Limit.



## OUR MISSION

Developing This Company As A Place For Personal Growth, Knowledge Enhancement, And Overall Development Of Its Employees, Stake Holders, And Customers Too.



## BECOME OUR CHANNEL PARTNER

With **INR 15.4L/ USD 19,250** Financial assistance from MIIGO

[VIEW JOINING PROCEDURE](#)



## EXPLORE YOUR CAREER AT MIIGO

Join us as a Sales Specialist / Digital Marketing Specialist/ Office Executive/ Sales Engineer

[VIEW JD & PACKAGE](#)



**FOLLOW/SUBSCRIBE,**  
LIKE & WRITE A HONEST FEEDBACK  
ON OUR PRODUCT



**BUY ANY PRODUCTS FROM THE BELOW BRANDS &  
GET 10% EXTRA DISCOUNT AS CV FROM MIIGO**



**DISTRIBUTOR/CHANNEL PARTNER**

**MIIGO ONLINE LLP**  
HYDERABAD, INDIA

✉ sales@miigo.online  
☎ +91-9398693085  
🌐 www.miigo.online

